



Encoding Guideline II:Clinical Algorithm

Susana Martins, MD MSc Samson Tu, MS Martha Michel, PhD





Available from previous sessions

- Formal statements to be encoded
- An ATP III knowledge base with
 - Concept hierarchy
 - Expressions: presence criteria, numeric criteria,
 N-ary criteria...
 - Eligibility criteria, goals, and patient characterization





Goals of this session

- Describe components of clinical algorithm
- Encode a collection of recommendations as a clinical algorithm
- Execute the clinical algorithm to generate patient-specific advice





Outline

- Describe Clinical Algorithm building blocks
- Workshop Activity: create clinical algorithms and use test cases to check recommendations






EON Clinical Algorithm

- Purpose: Generate recommendations
 - Messages
 - Drugs
 - Referrals
- Components:
 - Scenarios (starting point)
 - Decision nodes
 - Action-choice (recommendations) (endpoint)





Recap: Clinical algorithm








EON Clinical Algorithm

 Scenarios: <u>mutually exclusive</u> entry points for management decisions and actions







What makes "good" scenarios?

- Key determinants of management decisions
- Unambiguous definitions with reliable data
- Manageable number of starting points
- Explainable to clinicians

ATHENA HTN:

Not good: Therapeutic lifestyle change, co-morbidities


Possible: Classes of drugs, BP within/outside goal, number of drugs






Parts of a scenario

- New encounter: if true, evaluate scenario as a possible starting point
- Precondition: if evaluate to true, then use as starting point
- Followed by: next step in algorithm
- Consultation Template: scenario-specific messages











Modeling decisions

 Choice step: followed by action choices (possibly more than one preferred choice)



 Case step: evaluated expression determines which path to take








Modeling actions

- Action choice:
 - Rule in/out criteria
 - Define actions
 - Messages
 - Drug recommendations
 - Referrals...








Modeling preferences on actions

- Strict Rule Out
 Condition: Evaluated first. If true, action choice is ruled out
- Strict Rule In Condition: If true, action choice is preferred









Modeling actions

- Action specification- specifies actions that generate recommendations
- Example: add message










EON clinical algorithm

- Minimum Requirements:
 - Patient is eligible for the guideline
 - One new-encounter scenario must be applicable to patient case





Executing KB Test Environment







Workshop activity

- Construct clinical algorithm for Workshop Consensus (ATP III guideline)
 - Identify scenarios
 - Model decisions and actions
 - Run test patient case
- Structure: "See one, Do one together, Do one in pairs"





Brainstorming Scenarios: HINTS

- Manageable number of scenarios.
- Scenarios are mutually exclusive
- Reliable patient data
- Categorizing elements for scenarios: drug class (none, statins...), number of drugs, goal achieved?
- Create common pathways in a "simplified" way for maintenance purposes





Let's Create a Clinical Algorithm

- Patient scenario: Low Risk category on no lipid lowering drug
- Recommendations:
 - Order lipid profile
 - Encourage maintenance of therapeutic lifestyle changes
 - LDL not at goal, start therapeutic lifestyle changes
 - LDL not at goal, start lipid lowering therapy